MAFR200 series

AIR UNITS (F.R.UNIT)




MAFR200L



Specification:

Model	MAFR200	
Bore No.	6A	8A
Port size	PT 1/8	PT 1/4
Medium	Air	
Operating pressure range	0~9.9 kgf/cm^2 (0~0.99 MPa)	
Proof pressure	15 kgf/cm^2 (1.5 MPa)	
Effective orifice	7 mm^2	13 mm^2
Regulation pressure range	0.5~8.5 kgf/cm^2 (0.05~0.85 MPa)	
Ambient temperature	−5~+60℃ (No freezing)	
Filtration	Standard: 40 μm Option: 5 μm	
Attachment	Pressure gauge, bracket	
Weight	257 g, 226 g (MAFR200L)	

Symbol:



Order example:

MAFR200L − 6A − 1K − BSP

- MODEL
- BORE SIZE
  - **6A**: PT 1/8
  - **8A**: PT 1/4
- Adjustable Press. Range
  - Blank: Standard Type
  - **1K**: 0~1 kgf/cm^2
  - **2K**: 0~2 kgf/cm^2
  - **3K**: 0~3 kgf/cm^2
  - **4K**: 0~4 kgf/cm^2
- PORT THREAD
  - Blank: PT thread
  - **BSP**: BSP thread
  - **NPT**: NPT thread
- Blank: standard type
  L: Longer case, no case guard

Flow feature:

